

NSSTステンレス鋼管

日新製鋼ステンレス鋼管株式会社

http://www.nikkinko.co.jp

水道用ステンレス鋼管 (JWWA G 115)

SSP-SUS304 [屋内配管]

SSP-SUS316 [屋内配管及び地中埋設配管]

| 呼び径 SU | 外径 (m/m) | 肉厚 (m/m) | 重量 (kg/m) | |
|-----------|-------------|-------------|------------|------------|
| | | | SSP-SUS304 | SSP-SUS316 |
| 13 | 15.88 | 0.8 | 0.301 | 0.303 |
| 20 | 22.22 | 1.0 | 0.529 | 0.532 |
| 25 | 28.58 | 1.0 | 0.687 | 0.691 |
| 30 | 34.0 | 1.2 | 0.98 | 0.986 |
| 40 | 42.7 | 1.2 | 1.24 | 1.25 |
| 50 | 48.6 | 1.2 | 1.42 | 1.43 |

●長さは4mを定尺とします。

Ⓚ SUS316

一般配管用ステンレス鋼管 (JIS G 3448)

TPD-SUS304

| 呼び径 SU | 外径 (m/m) | 肉厚 (m/m) | 重量 (kg/m) |
|-----------|-------------|-------------|--------------|
| 13 | 15.88 | 0.8 | 0.301 |
| 20 | 22.22 | 1.0 | 0.529 |
| 25 | 28.58 | 1.0 | 0.687 |
| 30 | 34.0 | 1.2 | 0.98 |
| 40 | 42.7 | 1.2 | 1.24 |
| 50 | 48.6 | 1.2 | 1.42 |
| 60 | 60.5 | 1.5 | 2.2 |
| 75 | 76.3 | 1.5 | 2.79 |
| 80 | 89.1 | 2.0 | 4.34 |
| 100 | 114.3 | 2.0 | 5.59 |
| 125 | 139.8 | 2.0 | 6.87 |
| 150 | 165.2 | 3.0 | 12.1 |
| 200 | 216.3 | 3.0 | 15.9 |
| 250 | 267.4 | 3.0 | 19.8 |
| 300 | 318.5 | 3.0 | 23.6 |

●長さは4mを定尺とします。

Ⓚ

配管用ステンレス鋼管 (JIS G 3459)

鋼種記号A : SUS304、SUS304L他

鋼種記号B : SUS316、SUS316L他

単位 : kg/m

| 呼び径 | | 外径 | スケジュール5S | | | | スケジュール10S | | | | スケジュール20S | | | | スケジュール40S | | | | スケジュール80S | | | |
|-----|-------|-------|----------|-------|-------|------|-----------|-------|-------|------|-----------|-------|------|-------|-----------|------|------|------|-----------|---|------|--|
| | | | 厚さ | | 鋼種記号 | | 厚さ | | 鋼種記号 | | 厚さ | | 鋼種記号 | | 厚さ | | 鋼種記号 | | 厚さ | | 鋼種記号 | |
| A | B | mm | (mm) | A | B | (mm) | A | B | (mm) | A | B | (mm) | A | B | (mm) | A | B | (mm) | A | B | | |
| 10 | 3/8 | 17.3 | | | | | 2.0 | 0.762 | 0.767 | 2.0 | 0.762 | 0.767 | 2.5 | 0.922 | 0.928 | | | | | | | |
| 15 | 1/2 | 21.7 | 1.5 | 0.755 | 0.760 | 2.0 | 0.981 | 0.988 | 2.5 | 1.20 | 1.20 | 3.0 | 1.40 | 1.41 | 3.5 | | 1.59 | 1.60 | | | | |
| 20 | 3/4 | 27.2 | 1.5 | 0.960 | 0.966 | 2.0 | 1.26 | 1.26 | 2.5 | 1.54 | 1.55 | 3.0 | 1.81 | 1.82 | 4.0 | 2.31 | 2.33 | | | | | |
| 25 | 1 | 34.0 | 2.0 | 1.59 | 1.60 | 2.5 | 1.96 | 1.97 | 3.0 | 2.32 | 2.33 | 3.5 | 2.66 | 2.68 | 4.5 | 3.31 | 3.33 | | | | | |
| 32 | 1-1/4 | 42.7 | 2.0 | 2.03 | 2.04 | 3.0 | 2.97 | 2.99 | 3.0 | 2.97 | 2.99 | 3.5 | 3.42 | 3.44 | 5.0 | 4.70 | 4.73 | | | | | |
| 40 | 1-1/2 | 48.6 | 2.0 | 2.32 | 2.34 | 3.0 | 3.41 | 3.43 | 3.0 | 3.41 | 3.43 | 4.0 | 4.44 | 4.47 | 5.0 | 5.43 | 5.47 | | | | | |
| 50 | 2 | 60.5 | 2.0 | 2.91 | 2.93 | 3.0 | 4.30 | 4.32 | 3.5 | 4.97 | 5.00 | 4.0 | 5.63 | 5.67 | 5.5 | 7.54 | 7.58 | | | | | |
| 65 | 2-1/2 | 76.3 | 2.0 | 3.70 | 3.73 | 3.0 | 5.48 | 5.51 | 3.5 | 6.35 | 6.39 | 5.0 | 8.88 | 8.94 | 7.0 | 12.1 | 12.2 | | | | | |
| 80 | 3 | 89.1 | 2.0 | 4.34 | 4.37 | 3.0 | 6.43 | 6.48 | 4.0 | 8.48 | 8.53 | 5.5 | 11.5 | 11.5 | | | | | | | | |
| 90 | 3-1/2 | 101.6 | 2.5 | 6.17 | 6.21 | 3.0 | 7.37 | 7.42 | 4.0 | 9.72 | 9.79 | 6.0 | 14.3 | 14.4 | | | | | | | | |
| 100 | 4 | 114.3 | 2.5 | 6.96 | 7.01 | 3.0 | 8.32 | 8.37 | 4.0 | 11.0 | 11.1 | 6.0 | 16.2 | 16.3 | | | | | | | | |
| 125 | 5 | 139.8 | 3.0 | 10.2 | 10.3 | 3.5 | 11.9 | 12.0 | 5.0 | 16.8 | 16.9 | 7.0 | 23.2 | 23.3 | | | | | | | | |
| 150 | 6 | 165.2 | 3.0 | 12.1 | 12.2 | 3.5 | 14.1 | 14.2 | 5.0 | 20.0 | 20.1 | 7.0 | 27.6 | 27.8 | | | | | | | | |
| 200 | 8 | 216.3 | 3.0 | 15.9 | 16.0 | 4.0 | 21.2 | 21.3 | 6.5 | 34.0 | 34.2 | | | | | | | | | | | |
| 250 | 10 | 267.4 | 3.5 | 23.0 | 23.2 | 4.0 | 26.2 | 26.4 | 6.5 | 42.2 | 42.5 | | | | | | | | | | | |
| 300 | 12 | 318.5 | 4.0 | 31.3 | 31.5 | 4.5 | 35.2 | 35.4 | 6.5 | 50.5 | 50.8 | | | | | | | | | | | |

●長さは4mを定尺とします。

●上記寸法以外につきましては別途お問合せ下さい。